



DRUPALCON

*Portland*

MAY 20-24 2013

## What's New in Drush 6

Moshe Weitzman, Jonathan Hedstrom, Owen Barton

Building Bridges, Connecting Communities

# Output Formats



- Most commands support `--format` option
- Supported formats: `json`, `csv`, `export`, ...
- More formatters are easily added
- Command authors just return their data
- `drush topic docs-output-formats`





# Output Formats

```
$items['version'] = array(  
    'outputformat' => array(  
        'default' => 'key-value',  
        'pipe-format' => 'string',  
    ),  
);
```



# Roles and Permissions



- CRUD for roles
- Add remove permissions to roles
- Add/remove roles to users



# Config (D8)



- CRUD for config system
- Quickly Edit & Import



# Shell Aliases



'noncore' => 'pm-list --no-core'

'pulldb' => '!git pull && drush updb'

add to any drushrc.php



# drush[make]



```
api = 2
```

```
core = "7.x"
```

```
projects[ctools][version] = "1.3"
```

```
; http://d.org/node/1120028#comment-5792282
```

```
projects[ctools][patch][] = "http://p1.patch"
```

```
projects[views][version] = "3.7"
```



# New for 6.x



(most backported to 5.x)





# Local patches



- Patch copied into project directory



# Use a distribution as core



```
core = 7.x
```

```
projects[kickstart][type] = "core"
```

```
projects[kickstart][version] = "7.x-1.8"
```



# Quick Drupal can use a makefile



```
drush qd --makefile=mysite.make
```



# Per-project working-dir



```
projects[cap][download][revision] = "c9794ad"  
projects[cap][download][working-copy] = 1
```



# Set defaults



```
defaults[projects][subdir] = "contrib"
```

instead of:

```
projects[foo][subdir] = "contrib"
```

```
projects[bar][subdir] = "contrib"
```



# quick-drupal & runserver



- The quick-drupal (qd) command installs a throwaway Drupal site
- Drush core-runserver (rs) is a built-in web server (requires php-cgi, or php 5.4+)



# site-set



- Persists a site (local or remote) in your terminal without typing `@alias` each time
- Customize your prompt (PS1)
- In your `.bashrc`:  

```
source drush/drush.complete.sh  
PS1='\u@\h \w$(__drush_ps1 "[%s]")\$  
'
```



# user-login turbo



- Use a Drupal path as an argument and it will log you in any open that path in a single operation
- You can now reference target user by name, id or e-mail address





# Completion



- Completes almost everything in Drush
- Global options before command, command specific options after
- Your commands can provide argument completion too
- In your `.bashrc`

```
source path/drush/drush.complete.sh
```





DRUPALCON

*Portland*

MAY 20-24 2013

**What did you think?**

**Evaluate this session at:  
[portland2013.drupal.org/schedule](http://portland2013.drupal.org/schedule)**

**Thank you!**

Drupal is a registered trademark of Drupal Association (DrupalCamp)